

## Features:

1. Product series: LED panel lights series.
2. Brightness degradation: 3% - 5%1kh
- 3.No UV or IR radiation
- 4.Professional thermal management with Aluminium housing
- 5.Cool white, warm white, pure white are available
- 6.Can be ceiling or wall surface-mounted
- 7.Heat dissipation: two sides and back plate.
- 8.Diffuse angle: 180°.
9. Lifespan: 50,000 hours
- 10.WorkingTemperature: -25 ~ 45 degrees Celsius.
11. Widely used for Commercial Lighting,Office Lighting,Warehouse Lighting,Supermarket Lighting etc.



## LED Panel Light (SMD 3014)

Item No.	Picture	Size (L)X(W)X(H)mm	Voltage (V)	Body Color	Power (W)	QTY (pcs)	Led Type	Chip	Color	CCT(K)	Lumen (lm)	Beam Angle	Body Material	IP Grade	Ra	PF	Noise (Y/N)	Replace traditional light	Lifespan	Certificate	Warranty	Sample			Unit Price(USD/Piece)		
																						<10pcs	10-500pcs	>500pcs	10-500pcs	>500pcs	
LM-P302E10W-M		300x300x9.5mm	90-265V	Silver	10W	100	SMD3014	Epistar	Warm White	2800-3300K	720±30 lm	180°	Good heat Dissipation PCB (2.0)	IP44	≥75	≥0.95	N	50W	≥50000H	CE/RoHS	3 Years	US\$20.50	US\$19.50	US\$18.50			
LM-P302E10W-MW									Commercial White	4000-4500K	830±30 lm																
LM-P302E10W-W									White	5500-6000K	830±30 lm																
LM-P302E18W-M									Warm White	2800-3300K	1296±30 lm																
LM-P302E18W-MW									Commercial White	4000-4500K	1494±30 lm																
LM-P302E18W-W									White	5500-6000K	1494±30 lm																
LM-P306E24W-M		300x600x9.5mm	90-265V	Silver	24W	240	SMD3014	Epistar	Warm White	2800-3300K	1728±30 lm	180°	Good heat Dissipation PCB (2.0)	IP44	≥75	≥0.95	N	120W	≥50000H	CE/RoHS	3 Years	US\$45.50	US\$44.50	US\$43.50			
LM-P306E24W-MW									Commercial White	4000-4500K	1992±30 lm																
LM-P306E24W-W									White	5500-6000K	1992±30 lm																
LM-P306E30W-M									Warm White	2800-3300K	2160±30 lm																
LM-P306E30W-MW									Commercial White	4000-4500K	2490±30 lm																
LM-P306E30W-W									White	5500-6000K	2490±30 lm																
LM-P602E36W-M		600x600x9.5mm	90-265V	Silver	36W	360	SMD3014	Epistar	Warm White	2800-3300K	2592±30 lm	180°	Good heat Dissipation PCB (2.0)	IP44	≥75	≥0.95	N	180W	≥50000H	CE/RoHS	3 Years	US\$55.50	US\$54.50	US\$53.50			
LM-P602E36W-MW									Commercial White	4000-4500K	2988±30 lm																
LM-P602E36W-W									White	5500-6000K	2988±30 lm																
LM-P602E48W-M									Warm White	2800-3300K	3456±30 lm																
LM-P602E48W-MW									Commercial White	4000-4500K	3984±30 lm																
LM-P602E48W-W									White	5500-6000K	3984±30 lm																
LM-P3012E48W-M		300x1200x9.5mm	90-265V	Silver	48W	480	SMD3014	Epistar	Warm White	2800-3300K	3456±30 lm	180°	Good heat Dissipation PCB (2.0)	IP44	≥75	≥0.95	N	250W	≥50000H	CE/RoHS	3 Years	US\$58.50	US\$57.50	US\$56.50			
LM-P3012E48W-MW									Commercial White	4000-4500K	3984±30 lm																
LM-P3012E48W-W									White	5500-6000K	3984±30 lm																
LM-P3012E60W-M									Warm White	2800-3300K	4320±30 lm																
LM-P3012E60W-MW									Commercial White	4000-4500K	4980±30 lm																
LM-P3012E60W-W									White	5500-6000K	4980±30 lm																

- Price Term: EXW.
- Payment Term: T/T in advance
- Delivery: 3-5 days after order confirmed
- Quantitative sample: ≥1 PCS
- MOQ: 5 PCS
- Valid period :Two months